

## Certification

Kingbull piping systems have certificates from Australia SAI Global, French BV, Spanish AENOR, Swedish SP, Swiss SGS, ISO 9001, ISO 14001, China National Accreditation Service (CNAS) for Kingbull Lab, and other institutes. Kingbull piping products working life is 50 years and Kingbull provides customers 10 years quality warranty.



# Contents

Product Introduction	01
PVC-U Drainage Pipe Fitting	03
PVC-U Drainage Pipe Fitting and Tool	05
PVC-U Conduit Pipe Fitting	06
Installation	07

### Kingbull PVC-U Drainage pipe/PVC fire-retardant insulation electrical bushing pipe

Kingbull PVC-U drainage pipes, fittings and PVC fire-retardant insulation electrical bushing pipe are strictly manufactured according to GB/T5836.1-2006, GB/T5836.2 and ISO 3633, take vinyl chloride resin and some accessory ingredient as main material, add new environmental rigid particles modified anti-granules to make pipes be with better quality and impact resistance.

#### Advantages of PVC-U drainage pipes and fittings

- 1.The inner wall of the pipe is smooth and the flow volume can increase 30% compared to the cast-iron pipe in the conditions of same diameter and design grade.
- 2.The inner pipes and fittings will not have some change of infringement and shrinkage. The outside wall of the buildings will not be polluted by pipes which ensure the integrity of the buildings.
- 3.The weight is one fifth of the cast-iron pipeline so there is no need to use special lifting tools, which makes the transportation and installation more convenient. They are connected by gluewater and no fixed maintenance.
- 4.Using the PVC-U pipes and fittings will save the construction cost which is lower than the cast-iron pipeline system in the same specification.
- 5.PVC-U drainage pipe can work for more than 50 years under proper use and can be recycled.

#### PVC-U drainage pipe series

Name	specification (mm)	Item No
PVC-U drainage pipe series	50 × 2.0	1110001
	75 × 2.3	1110004
	110 × 3.2	1110007
	160 × 4.0	1110010
	200 × 4.9	1110013

Name	specification (mm)	Item No
PVC-U Spiral Silencing Pipe	75 × 2.3	1110004
	110 × 3.2	1110007
	160 × 4.0	1110010

#### Flame-retardant and insulation PVC electrical conduit series

Name	specification (mm)	Item No
PVC Medium electrical conduit	16 × 1.3	1110020
	20 × 1.4	1110021
	25 × 1.5	1110022
	32 × 1.6	1110023
PVC-U heavy electrical conduit	16 × 1.5	1110025
	20 × 1.6	1110026
	25 × 1.7	1110027
	32 × 1.8	1110028

Noted: The standard length of pipes is 4m.