

Normal Outside Diameter (d _n)		Wall Thickness (e _n)			
		SDR11		SDR17.6	
Basic Size	Tolerance	Basic Size	Tolerance	Basic Size	Tolerance
* 20	+0.3	3.0	+0.4	2.3	+0.4
	0		0		0
* 25	+0.3	3.0	+0.4	2.3	+0.4
	0		0		0
32	+0.3	3.0	+0.4	2.3	+0.4
	0		0		0
40	+0.4	3.7	+0.5	2.3	+0.4
	0		0		0
50	+0.4	4.6	+0.6	2.9	+0.4
	0		0		0
63	+0.4	5.8	+0.7	3.6	+0.5
	0		0		0
* 75	+0.5	6.8	+0.8	4.3	+0.6
	0		0		0
90	+0.6	8.2	+1.0	5.2	+0.7
	0		0		0
110	+0.7	10.0	+1.1	6.3	+0.8
	0		0		0
*125	+0.8	11.4	+1.3	7.1	+0.9
	0		0		0
160	+1.0	14.6	+1.6	9.1	+1.1
	0		0		0
*180	+1.1	16.4	+1.8	10.3	+1.2
	0		0		0
200	+1.2	18.2	+2.0	11.4	+1.3
	0		0		0
*225	+1.4	20.5	+2.2	12.8	+1.4
	0		0		0
250	+1.5	22.7	+2.4	14.2	+1.6
	0		0		0
315	+1.9	28.6	+3.0	17.9	+1.9
	0		0		0
355	+2.2	32.3	+3.4	20.2	+2.2
	0		0		0
400	+2.4	36.4	+3.8	22.8	+2.4
	0		0		0
450	+2.7	40.9	+4.2	25.6	+2.7
	0		0		0
500	+3.0	45.5	+4.7	28.4	+3.0
	0		0		0
560	+3.4	50.9	+5.2	31.9	+3.0
	0		0		0
630	+3.8	57.3	+5.9	35.8	+3.7
	0		0		0